

--2--

AMENDMENTS

IN THE CLAIMS:

Please cancel claim ~~29~~ without prejudice.

Please amend claims 1, 25 and 28 as indicated in Appendix A. The amended claims will then read as follows:

1. A modular microchannel apparatus for the chemical analysis of an analyte in a sample, comprising:

(a) a plurality of separation units each comprised of a solid substrate having a microchannel present in the surface thereof, wherein the microchannel in each separation unit is of a different length;

(b) a single reservoir unit in the form of a plate comprised of a reservoir that contains a liquid for introduction into the microchannels of the separation units; and

(c) an external power source operatively connected to the reservoir unit for driving the liquid from the reservoir through the microchannels of the separation units,

wherein the reservoir unit has dimensions that enable the operative and modular coupling of the reservoir unit to each separation unit in succession to allow liquid from the reservoir to be driven, by the external power source, into the microchannel of the separation unit that is operatively and modularly coupled to the reservoir unit.

25. A kit for making a modular microchannel apparatus for the chemical analysis of an analyte in a sample, comprising:

(a) a plurality of separation units each comprised of a solid substrate having a microchannel present in the surface thereof, wherein the microchannel in each separation unit is of a different length;

(b) a single reservoir unit in the form of a plate comprised of a reservoir that contains a liquid for introduction into the microchannels of the separation units; and

--3--

Sub 937  
E2  
(c) an external power source having dimensions that enable its modular and operative connection to the reservoir unit for driving the liquid from the reservoir through the microchannels of the separation units,

wherein the reservoir unit has dimensions that enable the operative and modular coupling of the reservoir unit to each separation unit in succession and to the external power source to drive liquid from the reservoir into the microchannel of the separation unit that is operatively and modularly coupled to the reservoir unit.

28. A modular microdevice for analyte analysis, comprising:

Sub 947  
(a) a plurality of separation units each comprised of a solid substrate having a microchannel present in the surface thereof, wherein the microchannel in each separation unit is of a different length;

E3  
(b) a single reservoir unit in the form of a plate comprised of a plurality of reservoirs, wherein each reservoir contains a liquid for introduction into a microchannel of a separation unit; and

(c) an external power source operatively connected to the reservoir unit for driving liquids from the reservoir unit through the microchannels of the separation units,

wherein the reservoir unit has dimensions that enable the operative and modular coupling of the reservoir unit to each separation unit in succession to allow liquid from at least one of the plurality of reservoirs to be driven, by the external power source, into the microchannel of the separation unit that is operatively and modularly coupled to the reservoir unit.

For the Examiner's convenience, the pending claims upon entry of this amendment are listed in Appendix B.

REMARKS

Claims 1-12, 25, 26 and 28-30 of this application were examined in the Office Action under reply, and stand finally rejected as follows: